


Crossword Collection II

Barbara Smith



EclipseCrossword.com

Across

6. Three hundred feet is the _ distance at which manholes should be installed for an 8-inch sewer line.
8. _ stands for cycles per second.
9. In a trench deep enough to require a ladder the worker must not be required to travel more than _ to get to a ladder.
11. A lantern ring in a pump _ gland will improve seat water distribution.
14. Another name for a lantern ring is _ ring.
15. The flushing water pressure in a water-lubricated wastewater pump should be at least _ psi more than the pump discharge pressure.
16. The bottom of a water line crossing above a sewer line must be _ inches from the crown of the sewer.
17. A mechanical ventilation system for the wet well portion of a lift station which operates continuously should be able to exchange the air in the wet well _ times an hour.

Down

1. The pH of 6.0 is _.
2. This is an acceptable means for applying herbicides to control roots in wastewater collection.

3. Leakage of seal water around the packing on a centrifugal pump is required because it acts as a(n) _.
4. According to "Ten States Standards" when a sewer line is installed parallel to a water line it must be a minimum of _ feet away.
5. This valve prevents any solution or water from backing up into a chlorine line.
7. An engineer must approve any trench shoring design above _ feet deep.
10. The minimum distance from the edge of the spoils to the edge of the trench is _ feet.
12. Important considerations when reviewing the plans for a lift station include _.
13. A(n) _ permit is required for any CSO outfall pipe.
15. Any excavation over _ feet deep must have a ladder for the worker to get in and out of the trench.